54. IWK

Internationales Wissenschaftliches Kolloquium International Scientific Colloquium



Information Technology and Electrical Engineering - Devices and Systems, Materials and Technologies for the Future



Faculty of Electrical Engineering and Information Technology

Startseite / Index:

http://www.db-thueringen.de/servlets/DocumentServlet?id=14089



### **Impressum**

Herausgeber: Der Rektor der Technischen Universität Ilmenau

Univ.-Prof. Dr. rer. nat. habil. Dr. h. c. Prof. h. c.

Peter Scharff

Redaktion: Referat Marketing

Andrea Schneider

Fakultät für Elektrotechnik und Informationstechnik

Univ.-Prof. Dr.-Ing. Frank Berger

Redaktionsschluss: 17. August 2009

Technische Realisierung (USB-Flash-Ausgabe):

Institut für Medientechnik an der TU Ilmenau

Dipl.-Ing. Christian Weigel Dipl.-Ing. Helge Drumm

Technische Realisierung (Online-Ausgabe):

Universitätsbibliothek Ilmenau

<u>ilmedia</u>

Postfach 10 05 65 98684 Ilmenau

Verlag:

isle

Verlag ISLE, Betriebsstätte des ISLE e.V.

Werner-von-Siemens-Str. 16

98693 Ilmenau

© Technische Universität Ilmenau (Thür.) 2009

Diese Publikationen und alle in ihr enthaltenen Beiträge und Abbildungen sind urheberrechtlich geschützt.

ISBN (USB-Flash-Ausgabe): 978-3-938843-45-1 ISBN (Druckausgabe der Kurzfassungen): 978-3-938843-44-4

Startseite / Index:

http://www.db-thueringen.de/servlets/DocumentServlet?id=14089

# NUMERICAL SIMULATION OF MAGNETOHYDRODYNAMIC PROBLEMS WITH FREE-SURFACE LIQUID METAL FLOW

### Ulrich Lüdtke

### Technische Universität Ilmenau

#### **ABSTRACT**

An important application of the MHD in material processing is to control the liquid metal flow including free surfaces. The magnetic field could be effectively used to produce the braking effect, the stirring effect and the shaping effect [1]. Thus the free surface in a liquid metal system could be controlled by a magnetic field. For the investigation of such processes we introduce a simulation tool for modeling flow problems under the influence of Lorentz forces. For the coupled field problem the self-developed program PROMETHEUS for solving Maxwell equations and the commercial program FLUENT for solving Navier-Stokes equations is used. The shape of the free surface, the flow in the melt and information about its stability are the subjects of interest. The results of the simulation of a liquid metal drop under the influence of a well defined magnetic field show a stationary free surface in good agreement with the experimental results [2].

### 1. INTRODUCTION

To show the possible field of application of this simulation tool some examples are presented. The present goal is the improvement of the efficiency of the two dimensional algorithm to prepare the extension of the tool to three dimensional problems. The Volume of Fluid method is used for the calculation of the free surfaces because the fixed grid of this method is very convenient for the coupling of the two programs.

# 2. COUPLING OF PROMETHEUS AND FLUENT

In a previous version PROMETHEUS and FLUENT worked on different computer systems and the necessary data were transferred via web. Therefore a very complicated program control was required [3]. In the recent version the self-developed finite element program PROMETHEUS is fully implemented in the user-defined-functions of FLUENT. This is very efficient because the data transfer between PROMETHEUS and FLUENT only happens in the memory of the computer and an external control

program for the coupling isn't necessary. The reason for doing this only now in a second version is the source code of PROMETHEUS, which had to be translated from the programming language Delphi to  $C_{++}$ 

The grid is created by the PROMETHEUS-tools and FLUENT imports the grid from PROMETHEUS. Before the start of the simulation tool a so-called "case file" must be created for the use of FLUENT. Material properties, boundary conditions, models and other necessary parameters are defined. PROME-THEUS gets the information about the free surface from FLUENT by the so-called volume fraction. The volume fraction is the percentage of galinstan of each element. The volume fraction ranges between 0 and 1. A value 1 indicates that the element is entirely consisting of galinstan while a value of 0 indicates an exclusively air-filled element. The volume fraction is used to weight the electric conductivity in the galinstan/air region. With this method the distribution of the electric current density is obtained. Some elements on the surface of the drop represent a lower current density than elements below the surface. This is based on the fact that most of the surface elements are not entirely consisting of galinstan, and therefore does not represent a disagreement between experimental and model results.

The hydro-dynamical flow of the metal drop is calculated depending on time. After each time step the change of the volume fraction is checked. If it exceeds a limit then the Lorentz-force are calculated by PROMETHEUS again. The calculation is carried out with sinusoidal field data implying the use of complex variable domains. It is possible to calculate the heat sources too therefore it is also possible to calculate the fluid flow including the temperature field. The simulation tool is able to calculate problems both in two-dimensional Cartesian or Cylindrical coordinates.

## 3. A FALLING LIQUID METAL DROP

Fig. 1 to Fig. 3 show the results of a simulation of a galinstan drop falling through an inductor with an alternating current of 2000A and a frequency of 10000Hz. Fig. 1 shows the magnetic flux lines when the drop is in the middle of the coil. No strong deformation of the flux lines is observable.




Figure 1 Magnetic flux lines, calculated by PROMETHEUS, time = 0.11s (see Fig. 3)






Figure 2 Lorentz-forces in the liquid metal drop, time = 0.11s (see Fig. 3)


No direct view to the geometry of the drop is possible by using PROMETHEUS. At the same point in time Fig. 2 shows the Lorentz-force trying to pinch the liquid metal drop. Fig. 3 shows the drop at various points in time. Caused by the Lorentz-force the deformation of the drop is clearly to observe. For a better analysis a video-animation of the falling drop can be used. Next steps could be parameter studies for the current or frequency.



Contours of Volume fraction (galinstan) (Time=0.0000e+00)Jun 12, 2006 FLUENT 6.2 (axi, dp, segregated, vof, lam, unsteady)



Contours of Volume fraction (galinstan) (Time=1.1000e-01) Jun 12, 2006 FLUENT 6.2 (axi, dp, segregated, vof, lam, unsteady)



Contours of Volume fraction (galinstan) (Time=1.3000e-01) Jun 12, 2006 FLUENT 6.2 (axi, dp, segregated, vof, lam, unsteady)




Figure 3 The liquid metal drop at various points in time




Figure 4 Magnetic flux lines, calculated by PROMETHEUS (see Fig. 6)




Figure 5 Lorentz-forces in the liquid metal drop (see Fig. 6)




Figure 6 The levitating liquid metal drop,

steady state

### 4. A LEVITATING LIQUID METAL DROP

Fig. 4 to Fig. 6 show the results of a simulation of a liquid metal drop with a dynamic viscosity of 1 Pas levitating in a pair of coils with an alternating current of 2000A and a frequency of 10000Hz. Fig. 4 shows the magnetic flux lines for this steady state. No strong deformation of the flux lines is observable.

Fig. 5 shows the liquid metal drop for the steady state. The Lorentz-force causes the deformation of the drop shown in Fig. 6. For a better analysis a video-animation of the falling drop can be watched. Next steps could be parameter studies for the current or frequency. Increasing the surface tension and the viscosity means to approach to a solid sphere.

### 5. CONCLUSIONS

The presented examples demonstrate the acceptability of the simulation tool for the calculation of moving liquid metal drops under the influence of Lorentzforces. The axis symmetric model doesn't allow any conclusion about the stability or instability in azimuthally direction. The present goal of the "Magnetofluiddynamik" research group is the extension of the simulation tool to three-dimensional implementation problems. The of the PROMETHEUS-code into FLUENT and optimisation of the coupling process are requirements for the extension to three-dimensional problems.

### 6. REFERENCES

[1] Brauer, H.; Halbedel, B.; Karcher, Ch.; Kolesnikov, Y.; Lüdtke, U.; Resagk, Ch.; Thess, A.: Magnetic control of fluid flows – hot topics in magneto-fluiddynamics, ICS-Newsletter 15 (3), 1-10, 2008.

[2] Brauer, H.; Lüdtke, U.; Thess, A.; Resagk, Ch.; Karcher, Ch.; Halbedel, B.: Studies of interactions of electroconductive fluids with electromagnetic fields, Proc. COMPUMAG 2007, Aachen, 867-868, 2007.

[3] Lüdtke, U.; Karcher, Ch.: Numerical simulation of a liquid metal drop under the influence of Lorentz-forces, International Scientific Colloquium, Modelling for Electromagnetic Processing, Hannover, March 24-26, 2003.