

Content-based Image Retrieval for Biodiversity: A Comparative Study


Nora Youssef¹, Alsayed Alzergawy², Ibrahim F. Moawad¹,
EL-Sayed M. EL-Horbaty¹, and Rania Elgohary¹

¹ Faculty of Computer and Information Sciences, Ain Shams University, Egypt



² Institute of Computer Science, Friedrich Schiller University of Jena, Germany




Introduction



Edge Feature



5 different edge types in image




- The global and semi-global edge histograms (5 and 65 bins)
- Combining (Local + Global + Semi-global) histograms = 150 bin histogram

- Distance measure [1]:


$$D(A, B) = \sum_{k=0}^{79} |Local_{A[i]} - Local_{B[i]}| + 5 \times \sum_{k=0}^4 |Global_{A[i]} - Global_{B[i]}| + \sum_{k=0}^{64} |Semi_Global_{A[i]} - Semi_Global_{B[i]}|$$

CBIR Block Diagram



[3] Lucene Image Retrieval

LIRE




[2] IMAGENET

Dataset

Synset	Id	#Images	Sample
Animal	n00015388	400	
Planet flora,			
planet life	n00017222	400	
Owl	n01621127	100	
Elephant	n02503517	100	

Experimental Evaluation

- Image Features
 - Fuzzy Color Texture Histogram (FCTH)
 - Color layout (CLD)
 - Edge Histogram
 - Combined Edges (CE)
 - CE + CLD
 - CE + FCTH
- Dataset size = 1000 image
- 13 different queries
- Results evaluated by 10 users



Conclusion

- Combined features have better semantic meaning than single ones.
- Semantic gap still exists
- (Future Work)** Machine learning techniques to limit search scope:
 - Clustering & Classification

References

- C. S. Won. Feature extraction and evaluation using edge histogram descriptor in mpeg-7. In Pacic-Rim Conference on Multimedia, pages 583-590. Springer, 2004
- J. Deng, W. Dong, R. Socher, L.-J. Li, K. Li, and L. Fei-Fei. ImageNet: A large-scale hierarchical image database. In Computer Vision and Pattern Recognition, 2009. CVPR 2009. IEEE Conference on, pages 248-255. IEEE, 2009.
- M. Lux. Content based image retrieval with lire. In Proceedings of the 19th ACM international conference on Multimedia, pages 735-738. ACM, 2011.

Acknowledgments: This work was done at the SWEP course, as a part of the BioDialog project. This project, is funded by DAAD at Friedrich Schiller University Jena. Special thanks to Prof. Birgitta König-Ries.



nora.youssef@cis.asu.edu.eg
nora.abdelmageed@uni-jena.de



FRIEDRICH-SCHILLER-
UNIVERSITÄT
JENA



DAAD