

Hagedorn, Stefan; Räth, Timo; Birli, Oliver; Sattler, Kai-Uwe:

Processing large raster and vector data in apache spark

Original published in: Datenbanksysteme für Business, Technologie und Web / BTW 18. 2019 Rostock. - Bonn : Gesellschaft für Informatik e.V., [2019]. - 289 (2019), p. 551-554.
ISBN 978-3-88579-683-1
(GI-Edition. Proceedings / Gesellschaft für Informatik ; 289)

Original published: 2019

ISSN: 1617-5468

DOI: [10.18420/btw2019-43](https://doi.org/10.18420/btw2019-43)

[Visited: 2020-02-27]



This work is licensed under a [Creative Commons Attribution-ShareAlike 4.0 International license](https://creativecommons.org/licenses/by-sa/4.0/). To view a copy of this license, visit <http://creativecommons.org/licenses/by-sa/4.0/>

Processing Large Raster and Vector Data in Apache Spark

Stefan Hagedorn¹, Timo Räth¹, Oliver Birli², Kai-Uwe Sattler¹

Abstract: Spatial data processing frameworks in many cases are limited to vector data only. However, an important type of spatial data is raster data which is produced by sensors on satellites but also by high resolution cameras taking pictures of nano structures, such as chips on wafers. Often the raster data sets become large and need to be processed in parallel on a cluster environment. In this paper we demonstrate our STARK framework with its support for raster data and functionality to combine raster and vector data in filter and join operations. To save engineers from the burden of learning a programming language, queries can be formulated in SQL in a web interface. In the demonstration, users can use this web interface to inspect examples of raster data using our extended SQL queries on a Apache Spark cluster.

1 Introduction

An enormous number of spatial and spatio-temporal data objects is produced every second by thousands or even millions of sources. This data is represented as vector objects (i. e. a single point, a sequence of points that form a line string or polygon) or raster data. Raster data sets are created, e. g. by sensors and cameras where each pixel of the camera sensor is stored as a value in the data set.

Large raster data sets are produced by satellites observing the Earth and by high resolution cameras taking pictures of nano-sized structures – as performed in the Nano Positioning and Measurement Machines (NPMM)³[Ba14; Ha02]. Depending on camera resolution and magnification, the NPMM200 at TU Ilmenau produces data sets up to 17 TB per object, which cannot be handled by single node DBMSs anymore.

For managing and processing raster data special purpose DBMSs have been proposed in the past, e. g. SciDB [Br10] or RasDaMan [Ba98]. Popular platforms for very large data sets are Hadoop MapReduce and Apache Spark. However, since their generic data model is not able to utilize characteristics of spatial objects (neighborhood, distances, etc.), extensions that add spatial *vector*-only data support have been proposed [EM15; YWS16]. Rasterframes⁴ is the only system that supports raster data. The combination of raster and vector data, however, is limited to range queries only.

¹ Technische Universität Ilmenau, Databases & Information Systems, Ilmenau, first.last@tu-ilmenau.de

² Technische Universität Ilmenau, PMS, Ilmenau, first.last@tu-ilmenau.de

³ <https://www.tu-ilmenau.de/cc-npmm/>

⁴ <http://rasterframes.io/>

of the represented rectangle and the resolution. Vector data objects are represented using a `STObject` class that stores the geometric object (point, polygon, etc.) as well as a temporal component.

A filter operator on a raster data set expects a `STObject` (or a plain rectangle) as query range. As a result, the operator finds all tiles that match the query range according to the provided predicate (intersects, contains, etc.) and returns them as a new `RasterRDD`. The explicit storage of the meta information (position, width, height) in each tile allows for an independent data parallel processing of all tiles. As shown in Fig. 2, a tile may only partially intersect with a polygonal query range and hence, the resulting tiles may be of different extents. This new information is saved into the resulting tiles T'_1, T'_2 etc. The rectangular result tiles of the filter operation represent the minimum bounding rectangle of the intersection with the query range and the input tile. Pixel values in the result tile that do not match the predicate, are set to `NULL` or a `NODATA` constant.

Besides the filter, `RasterRDDs` and `SpatialRDDs` can be joined with another `SpatialRDD`. Similar to the filter, the join operation finds all tiles (or `STObjects`) from the left input that have a join partner in the right input. In `STARK`, tiles are vectorized into rectangles using their stored meta information when their relation with instances of `STObject` has to be computed in filters and joins.

Operators are supported by spatial and temporal partitioners to assign data objects to worker nodes respecting their spatial and temporal neighborhood. Operators additionally benefit from a partition-local spatial or temporal indexing.

The web frontend is specifically designed to let users explore the raster and vector data sets with SQL. Users can define their relations by providing the path in the file system and the schema. The formulation of the spatial filter conditions is aided by a graphical selection tool that displays the spatial component (raster or vector) and lets users draw their region of interest. The SQL query is executed on a Spark cluster using our `STARK` framework. Results of the query can either be displayed in tabular form or as pictures (from raster tiles), on maps (vector objects), or charts. Users can select what and how attributes from the result should be visualized. Image rendering is performed by `STARK` (rather than by the browser) to account for large data sets.

3 Demonstration

We present our prototype designed to support scientists and engineers working with large spatial raster and vector data sets. A screenshot of the web frontend is shown in Fig. 3. During the demonstration users can interact with the web application: We will prepare real high resolution raster data sets captured by the NPMM as well as satellite images. Users can run queries (our predefined or their own ones) that show the various features of the `STARK` framework itself as well as the capabilities of the web interface. The queries

The screenshot displays the STARK web interface. At the top, 'Datasets' are listed: 'hdfs://data/nano/messung1/' pointing to 'wafers' and 'hdfs://data/regions/' pointing to 'regions'. Below this is a 'Query' section with tabs for 'SQL' and 'Scala'. The 'Geo Select' button is circled in red, with a red arrow pointing to the SQL query: `SELECT w.tile, r_maxvalue(w.tile) FROM wafers w, regions r WHERE r_intersects(w.tile, r.geo) AND st_contains($refgeo, r.geo)`. To the right is a 'Schema' section showing the structure of 'wafers' (tile: Tile) and 'regions' (id: Int, name: String, geo: STObject). Below the query is the 'Results' section, which includes a 'Table' view showing a thumbnail of a wafer and a 'Visualization' view showing a bar chart of 'r_maxvalue(w.tile)' for tiles 19-29. On the far right, 'Query Statistics' shows 'Progress' at 100%, 'Elapsed Time' of 52 seconds, and 'No. Rows' of 1583252.

Fig. 3: The user interface for querying raster data with SQL. With Geo Select users can use a graphical tool to select a region of interest, referred to in the `$refgeo` variable.

demonstrate STARK's unique feature of combined processing of raster and vector data on the Spark platform whereas the web interface lowers the entrance barrier of creating and submitting jobs to a cluster. Furthermore, users can choose from a list of available charts how results should be visualized and dynamically add them to the web page.

References

- [Ba14] Balzer, G. F.: Entwicklung und Untersuchungen zur 3-D-Nanopositioniertechnik in großen Bewegungsbereichen, PhD thesis, TU Ilmenau, 2014.
- [Ba98] Baumann, P.; Dehmel, A.; Furtado, P.; Ritsch, R.; Widmann, N.: The multidimensional database system RasDaMan. In: SIGMOD Rec. 1998.
- [Br10] Brown, P. G.: Overview of sciDB: Large Scale Array Storage, Processing and Analysis. In: SIGMOD. Pp. 963–968, 2010.
- [EM15] Eldawy, A.; Mokbel, M. F.: SpatialHadoop: A MapReduce Framework for Spatial Data. In: ICDE. Seoul, 2015.
- [Ha02] Hausotte, T.: Nanopositionier- und Nanomessmaschine, PhD thesis, TU Ilmenau, 2002.
- [HGS17] Hagedorn, S.; Goetze, P.; Sattler, K.-U.: The STARK Framework for Spatio-Temporal Data Analytics on Spark. In: BTW. Pp. 123–142, 2017.
- [YWS16] Yu, J.; Wu, J.; Sarwat, M.: A demonstration of GeoSpark: A cluster computing framework for processing big spatial data. In: ICDE. Pp. 1410–1413, 2016.